



## ARRI ALEXA XT B+W SPECIFICATIONS

Sensor Modes	16:9, 4:3
Maximum number of sensor photo sites	2880 x 2160
Exposure latitude (stops)	15
Base sensitivity (EI)	2000
White balance (fixed)	2000
Exposure Index (EI)	160 - 3200
Frame rate 16:9 (fps)	0.75 - 120
Frame rate 4:3 (fps)	0.75 - 90
Sound level	< 19 db (A)
Electronic shutter angle (degrees)	5 - 358
Weight (Kg/lbs)	8.7/19.2
Electronic viewfinder	Yes
Optical viewfinder	No
In-camera recording to SxS PRO cards	No
In-camera recording to XR Capture Drives	Yes
In-camera recording to CFast 2.0 cards	No
ARRIRAW recording	In-camera
In-camera ProRes HD recording	No
In-camera ProRes 2K recording	No
In-camera DNxHD HD recording	No
ProRes Pre-recording	No
Integrated CDL Server	Yes
Lens Data System	Yes
HD-SDI video output connectors	4
24 V accessory power connectors (RS)	3
Integrated wireless camera and lens control	Yes
Tilt and roll sensors	Yes
Electronic horizon	Yes
Behind the lens ND filter(18)	BG39 (B+W), BG87C (IR pass)